


MAX Splice Cassette SC Tray for 12 crimp splice protector, pack of 6

CORNING

Part Number:
S46998-A002-R497

The MAX system can be used with either single circuit (SC) or single element (SE) trays or a mixture of both, in accordance with the network requirements. Corning recommends the usage of SC trays. In a Single Element (SE) Network, the fibers from one buffer tube are always stored in one single splice tray. Most network operators are still using 12 fibers per tube. In addition the fibers from up to 6 individual customer drop cables are also guided to one single splice tray. In this case, if maintenance is later required then all the fibers must be taken out of the splice tray. Also, even though the maintenance work may only involve one customer, the maintenance work may often affect the other 5 customers' connections too. With SC Systems this entire risk is eliminated by only using 1 customer per splice tray. One raster unit is required for the SC tray and two are required for the SE tray. Two SC trays can be replaced by one SE tray or vice versa. Additional trays for optical splitters, water sensors or mechanical splices are available. Especially for optical splitter Corning recommends the usage of colored splice trays. The splice trays provide a complete fiber management system with overlength storage, bending control and the possibility of changing the fiber direction. Splice trays can be equipped with numbered and colored rings; thus providing fast and secure access.



MAX Splice SC Tray for 12 crimp splice protector, pack of 6

MAX Splice Cassette SC Tray for 12 crimp splice protector, pack of 6

CORNING

Specifications

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Maximum number of fibers	12
System	MAX
Splice Tray Type	MAX Splice Tray
Splice Protectors Type	Crimp

Dimensions

Height	5 mm
Width	155 mm
Depth	105 mm
Weight	0.1 kg

Ordering Information

Product Number	S46998-A002-R497
Shipping Height	30 mm
Shipping Width	170 mm
Shipping Depth	115 mm
Units per Delivery	6/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.